



FREEDOM STACKER



TECHNICAL FEATURES

- 260kg capacity at 300mm load centre
- 1600mm lift
- Battery electric operation
- Standard attachments available are: - adjustable forks, platform, roller platform and boom (all mild steel).
- Bespoke attachments are also available i.e. reel handler and dual position carriage:- POA
- Ergonomically designed handles to improve manoeuvrability
- Modular, mild steel design capable of fitting most applications
- High Specification
- Un-rivalled price against specification
- Simple Maintenance 'plug and play' components
- Problem Solver - lifts most plastic boxes with ease
- Compact - fits through a standard doorway
- High visibility with a single, narrow mast
- Safe to load as it has twin total stop brakes



TECHNICAL SPECIFICATION

	Overall height - raised	Overall height - closed	Handle height	Handle width	Overall length	Fork length	Fork height - raised - P1	Fork height - raised - P2*	Fork height - lowered - P1	Fork height - lowered - P2*	Overall width	Width over Fork	Castor wheel diameter	Load wheel diameter
	A	B	C	D	E	F	G	G	H	H	I	J	-	-
Freedom stacker	2245	1960	1295	350	1100	550	1600	1950*	90	440*	715	520	125	80

* Dual position carriage
 All dimensions are in mm unless otherwise shown

