



Specifications

Model	GS-3384 RT	
Measurements	Metric	US
Working height maximum*	11.94 m	39 ft 2 in
A Platform height maximum	9.94 m	32 ft 6 in
B Platform height - stowed**	1.55 m	5 ft 1 in
C Platform length outside:		
extended - single deck	3.98 m	13 ft .5 in
extended - dual deck	5.34 m	17 ft 6.25 in
extended - super deck	6.57 m	21 ft 6.5 in
extended - super deck	7.38 m	24 ft 2.5 in
D Slide-out platform extension deck - front	1.52 m	5 ft
E Slide-out platform extension deck - rear	1.22 m	4 ft
F Platform width - outside	1.83 m	6 ft
G Height - stowed: folding guardrails	2.68 m	8 ft 9.5 in
rails lowered	2.0 m	6 ft 6.75 in
H Length - stowed: single deck	3.94 m	12 ft 11.25 in
dual deck	3.98 m	13 ft 5 in
super deck	4.81 m	15 ft 9.5 in
with outriggers	4.88 m	16 ft
Length - extended: single deck	5.40 m	17 ft 9 in
dual deck	6.57 m	21 ft 6.5 in
super deck	7.38 m	24 ft 2.5 in
I Width	2.13 m	7 ft
J Wheelbase	2.84 m	9 ft 4 in
K Ground clearance - center	0.33 m	13 in

Productivity

Maximum platform occupancy	7	7
Lift capacity	1,134 kg	2,500 lbs
Drive height	full height	full height
Drive speed - stowed	6.4 km/h	4.0 mph
Drive speed - raised	1.1 km/h	0.7 mph
Gradeability - stowed***	50%	50%
Maximum outrigger levelling****	7°(front to back)/12°(side to side)	
Turning radius - inside	3.09 m	10 ft 1.5 in
Turning radius - outside	5.94 m	19 ft 6 in
Raise/lower speed	45/29 sec	45/29 sec
Controls	proportional	proportional
Drive	four wheel	four wheel
Tyres - foam-filled rough terrain	25 x 79 cm	10 x 31 in

Power

Power source	Deutz D2011L03i 3 cylinder diesel 36 kW (49 hp) air cooled	
Auxiliary Power unit	12 V DC	12 V DC
Fuel tank capacity	113.6 L	30 gal
Hydraulic system capacity	113.6 L	30 gal

Sound & Vibration Levels

Sound pressure level (ground workstation)	88 dBA	88 dBA	88 dBA	88 dBA
Sound pressure level (platform workstation)	78 dBA	78 dBA	78 dBA	78 dBA
Vibration	<2.5 m/s ² 8 ft 2 in/s ²		<2.5 m/s ² 8 ft 2 in/s ²	

Weight*****

CE base machine	5,445 kg	12,002 lbs
The basic unit has the single extension deck, diesel motor, no outriggers, foam-filled or non-marking tyres, CE link guard and CE load sense.		
Unit weight modifiers for options		
Outriggers*****	add 760 kg	1,675 lbs
Dual Extension decks	add 356 kg	784 lbs
Super decks	add 411 kg	906 lbs
Generator	add 48 kg	105 lbs

Standards Compliance

EU Directives: 2006/42/EC - Machinery
(harmonized standard EN280:2013); 2004/108/
EC (EMC); 2000/14/EC (Outdoor Noise)

* The metric equivalent of working height adds 2 m to platform height.

** Based on RT tyres. Deduct 5.08 cm (2 in) for non-marking tyres.

*** Gradeability applies to driving on slopes. See operator's manual for details regarding slope ratings.

**** Outriggers are optional.

***** Weight will vary depending on options and/or country standards.

Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
<p>Measurements</p> <ul style="list-style-type: none"> • 11.94 m (39 ft 2 in) working height • Up to 1,134 kg (2,500 lbs) lift capacity <p>Productivity</p> <ul style="list-style-type: none"> • Diamond plate deck • Replaceable aluminum deck • Folding guardrails • Two self-closing full-height swing gates • Proportional lift and drive • Onboard diagnostic system • Hydraulic oil cooler • AC power to platform • Positive traction control • Four-wheel braking • Tilt level sensor with audible alarm • Descent alarm • Flashing beacons • Horn • Hour meter • Certified load sensor • Telematics-Ready Connector <p>Power</p> <ul style="list-style-type: none"> • All engines are emissions compliant • 12V DC auxiliary power • Slide-out engine tray 	<p>Platform Options</p> <ul style="list-style-type: none"> • 3.98 x 1.83 m (13 ft 0.5 in x 6 ft) steel frame platform (standard) • 1.52 m (5 ft) slide-out extension deck (standard) • Dual slide-out platform extension deck package⁽¹⁾, 1.52 m (5 ft) front and 1.22 m (4 ft) rear (optional) • 7.38 m (24 ft 2.5 in) super deck platform extension package^(1,2) (optional) <p>Outrigger Options</p> <ul style="list-style-type: none"> • Automatic levelling hydraulic outriggers⁽¹⁾ • No outriggers (standard) <p>Engine Options</p> <ul style="list-style-type: none"> • Deutz diesel 36 kw (49 hp) <p>Drive Options</p> <ul style="list-style-type: none"> • 4 x 4 <p>Axle</p> <ul style="list-style-type: none"> • Non oscillating <p>Tyre Options</p> <ul style="list-style-type: none"> • Foam-filled rough terrain (standard) • Foam-filled, non-marking rough terrain 	<p>Productivity Options</p> <ul style="list-style-type: none"> • Air line to platform • Power to platform (incl. plug, socket and ground fault interrupt leakage on request) • Biodegradable hydraulic oil⁽¹⁾ • Track & Trace⁽³⁾ (GPS unit providing machine location & operating information) • Motion alarm <p>Power Options</p> <ul style="list-style-type: none"> • Diesel catalytic scrubber muffler • Low temperature cut-out module • Engine heater⁽⁴⁾



⁽¹⁾ Factory fit option only
⁽²⁾ Requires automatic levelling outriggers
⁽³⁾ Includes a first 2 years subscription
⁽⁴⁾ Available with Deutz engine only