




Aerial Work Platforms

IWP™ Super Series™

Specifications



Models	IWP-20S		IWP-25S		IWP-30S	
Measurements	Metric	US	Metric	US	Metric	US
Working height*	8.15 m	26 ft 2 in	9.44 m	30 ft 5 in	11 m	35 ft 6 in
Platform height	6.15 m	20 ft 2 in	7.44 m	24 ft 5 in	9 m	29 ft 6 in
A Horizontal outreach**	66 cm	2 ft 2 in	—	—	—	—
B Height - stowed:						
fully lowered	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in	1.93 m	6 ft 4 in
base raised	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in
C Length	1.52 m	5 ft	1.52 m	5 ft	1.52 m	5 ft
D Width - standard base	81 cm	2 ft 8 in	81 cm	2 ft 8 in	—	—
wide base	—	—	—	—	1.02 m	3 ft 4 in
Corner access***	15 cm	6 in	15 cm	6 in	18 cm	7 in

Productivity

Lift capacity	159 kg	350 lbs	159 kg	350 lbs	159 kg	350 lbs
Platform Dimensions (l/w/h)						
Standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated standard	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in	69/66/114 cm	27/26/44.75 in
Gated narrow	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in	66/51/114 cm	26/20/44.75 in
Standard fiberglass**	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in	74/67/110 cm	29/26.5/43.5 in

Power

AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12V

Sound & Vibration Levels

Sound pressure level						
(ground workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Sound pressure level						
(platform workstation)	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA	<70 dBA
Vibration	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²	<2.5 m/s ²	<8 ft 2 in/s ²

Weight****

Standard base						
AC	565 kg	1,245 lbs	585 kg	1,290 lbs	—	—
DC	610 kg	1,345 lbs	630 kg	1,390 lbs	—	—
Standard base with outreach option						
AC	612 kg	1,350 lbs	—	—	—	—
DC	658 kg	1,450 lbs	—	—	—	—
Wide base						
AC	—	—	—	—	649 kg	1,430 lbs
DC	—	—	—	—	694 kg	1,530 lbs

Standards Compliance

EU Directives: 2006/42/EC - Machinery (harmonized standard EN280:2013); 2004/108/EC (EMC); 2006/95/EC (LVD)

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Fiberglass platforms are not available with the outreach option.

*** Corner of platform top rail to corner of wall with ability to rotate leveling jack handle.

**** Weight will vary depending on options and/or country standards.



Aerial Work Platforms

IWP™ Super Series™

Features

Standard Features	Easily Configured To Meet Your Needs	Options & Accessories
Measurements IWP-20S <ul style="list-style-type: none">• 8.24 m (26 ft 6 in) working height• 6.24 m (20 ft 6 in) platform height• 81 cm (2 ft 8 in) standard base width• Outreach option adds 66 cm (2 ft 2 in) of horizontal reach• Up to 159 kg (350 lbs) lift capacity IWP-25S <ul style="list-style-type: none">• 9.44 m (30 ft 5 in) working height• 7.44 m (24 ft 5 in) platform height• 81 cm (2 ft 8 in) standard base width• Up to 159 kg (350 lbs) lift capacity IWP-30S <ul style="list-style-type: none">• 11 m (35 ft 6 in) working height• 9 m (29 ft 6 in) platform height• 1.02 m (3 ft 4 in) wide base width• Up to 159 kg (350 lbs) lift capacity	Platform Options <ul style="list-style-type: none">• Sliding mid-rail platform (standard)• Gated standard platform• Gated narrow platform• Standard fiberglass platform (not available with outreach) Power Options <ul style="list-style-type: none">• AC power 85V / 50-60 Hz• AC power 110V / 50-60 Hz• AC power 220V / 50-60 Hz• DC power with worldwide automatic “smart” charging system (12V / 110V / 230V / 50-60 Hz) Base Options <ul style="list-style-type: none">• Standard base (IWP-20S and 25S only)• Wide base (IWP-30S only)	Productivity <ul style="list-style-type: none">• Outreach option (IWP-20S only)⁽³⁾• Power to platform (plug, socket and ground fault interrupt leakage on request)• Operational warning light and descent alarm package• Tool tray⁽¹⁾• Fluorescent tube caddy⁽¹⁾• Platform locating laser light⁽¹⁾ Power <ul style="list-style-type: none">• Power wheel assist with dual battery package^{(2) (3)}• Dual battery package⁽³⁾

Productivity

- Auxiliary platform lowering
- Most rigid mast in the industry
- Standard base rolls through standard doorways
- Wide base rolls through double doorways
- AC power to platform
- Dual activated up/down switch
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Built-in level sensing with interlocks



⁽¹⁾ Available on selected models only. See your Genie representative for further information.

⁽²⁾ Adds 32 cm (12.5 in) to unit length and 129 kg (285 lbs) to unit weight.

⁽³⁾ Factory-fit option only.

Distributed By

CHERRY PICKER 
Ireland's Leading Supplier of Access Platforms



cherrypicker.ie



sales@cherrypicker.ie



353 (1) 835 4788



353 87 255 7755