



## LIGHT DUTY SCISSOR LIFT




- The 150kg scissor tables are light, portable, highly manoeuvrable and easy to use.
- Available in super lightweight aluminium or steel
- Lifts to a height of 780mm
- Folds flat for easy transportation and storage
- Hinged handle automatically locks into upright position, released by foot bar
- Manual operation
- Particularly suited to office and pharmaceutical environments
- Optional extras are available such as a roller top or bellows skirt
- Manufactured to conform to EU Standards BSEN 1570 and BS:5323:1980

## TECHNICAL FEATURES

- Can be used safely at any height
- Fitted with a total stop brake as standard to prevent the table from moving when being unloaded
- Unique lift up table top allows safe and easy maintenance- can only be lifted when table in a closed position
- All models fitted with an overload valve and slow lowering valve to control lowering speed
- Rubber non-marking tyres to prevent damage to floors
- Wheels fitted with thread guards
- Epoxy powder coated finish for durability
- Issued with a test certificate

## WARNINGS

- Scissor tables are NOT designed to carry people- special safety features would be required in accordance with EN1570
- Tables which carry wheeled loads or rolling loads must be fitted with a device to prevent these rolling off
- Mobile tables are designed to be propelled by pedestrians, if any other means are to be used please use precautions in accordance with EN1570
- The rated load of the table must not be exceeded as this can cause damage to the table. The load must be evenly distributed on the table surface for stability.



## TECHNICAL SPECIFICATION

| Model     | C<br>Raised<br>Height | B<br>Closed<br>Height | E x A<br>Platform<br>W x L | E x D<br>O/A<br>W x L | F<br>Handle<br>Height | Wheel<br>Dia | Approx<br>Weight<br>(KG) | Reference             | Approx<br>Pumps to<br>Lift Height |
|-----------|-----------------------|-----------------------|----------------------------|-----------------------|-----------------------|--------------|--------------------------|-----------------------|-----------------------------------|
| STEEL     | 780                   | 255                   | 450 x<br>760               | 450 x<br>990          | 940                   | 125          | 41                       | SC-150-S-M            | 14                                |
| ALUMINIUM | 780                   | 255                   | 450 x<br>760               | 450 x<br>990          | 940                   | 125          | 27                       | SC-150-S-M-<br>ALU-PC | 14                                |

All dimensions are in mm unless otherwise shown

| Options  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Second Braked wheel</li> <li>• Stainless Steel top cover</li> <li>• Plastic roller conveyor top (Increases closed/raised height by 60mm)</li> <li>• Ball top</li> <li>• Bellows safety skirt</li> <li>• Rubber Mat</li> </ul> |  |

