



STOCK PICKER 40 PUSH

Capacious, practical and secure

The picking machine with an elevation of up

to 4 meters, having manual traction and automatic elevation with a 24-volt battery. Made entirely in aluminum, it is extremely maneuverable and compact. The large-dimension picking platform can be adjusted in height, even whilst aboard, thanks to a manual remote control.

The picking platform





- The load can also be lifted by remote control whilst on the platform
- 2. Large extendible loading platform of up to 66 x 92 cm

Maneuverable, easy to move





STOCK PICKER 40 PUSH

110 + 40 Kg

internal & external 1440 mm

310 mm

1960 mm

© 353 (1) 835 4788

sales@cherrypicker.ie (C) 353 87255 7755

cherrypicker.ie



4 Mt -

3 Mt -

2 Mt

1 Mt -

	D	Overall machine dimensions	995 mm
Taraone A	Е	1	1640 mm
	F]	740 mm
	G	Cage inner dimensions	700 mm
	Н	1	680 mm
650 ,270,	Picking platform		450 mm
			660 mm
		у	270 mm
			660 mm
		late capacity	40 Kg
		weight	172 Kg
		M 12 V batteries	33 Ah* - 45 Ah**
		ipply	24 V
0 1 Mt 2 Mt	Battery charger		110 V - 120 V
	I	Maximum climbing ability	15%
4 Mt 650 270 3 Mt	Swivel w	heels dimensions	Ø 100 x 30
	Swivel wheels dimensions		Ø 150 x 45
	Turning radius		0
	Maximum rising speed		0,08 m/s
		n descending speed	0,1 m/s
2 Mt _ 925 _ 8	Work cycles (with fresh batteries)		100 - 150
1 Mt 450 270	* Standard Optional - 40BGM *** By work cycle we mean a self-propelled movement of 20 m with a full ascent to and descent from the maximum height		

600

Max capacity Number of people

Stowed height

platform level

platform level

Min. height from the ground to the

Max. height from the ground to the

Use

B

C