



## Electric Motor Drive Scissor Lifts

(HYDRAULIC MOTOR DRIVE PRICES/SPECS AVAILABLE UPON REQUEST)

### PRODUCT SPECIFICATION

Model	CP1230 E	CP1432 E	CP1832 E	CP1930 E	CP2632 E	CP2646 E	CP3246 E	CP4046 E
Lift Capacity(kg)	240	230	230	230	230	450	320	320
Lift Capacity Extension(kg)	113	113	113	120	113	113	113	113
Max. Platform Occupants	2	2	2	2	2	2	2	2
Max. Working Height(A+2)(m)	5.6	6.3	7.5	7.8	10	10	12	14
Overall Length(B)(m)	1.53	1.53	1.53	1.86	2.4	2.42	2.47	2.47
Overall Width(C)(m)	0.76	0.81	0.81	0.76	0.83	1.18	1.18	1.18
Overall Height-Rails Folded(m)	1.82	1.9	2	1.84	1.95	1.73	1.86	1.99
Overall Height-Rails Onfolded(m)	2.06	2.15	2.275	2.14	2.32	2.3	2.43	2.56
Platform Extension Length(m)	0.6	0.6	0.6	0.9	0.9	0.9	0.9	0.9
Driving Speed (stowed/raised)(km/h)	4/0.5	4/0.5	4/0.5	4/0.8	3.5/0.8	4/0.8	4/0.8	4/0.8
Up/Down Speed-GB(sec)	/	/	/	16/28	31/40	/	62/48	65/60
Up/Down Speed-CE(sec)	25/18	25/20	32/27	16/28	31/40	35/40	58/48	58/60
Gradeability(%)	25	25	25	25	25	25	25	25
Max. Slope(°)	1.5/3	1.5/3	1.5/3	1.5/3	1.5/3	1.5/3	2/3	1.5/3
Machine Weigh(kg)	880 915(PB)	970 985(PB)	1300	1610	2140	2715	3000	3300



- ✔ Optimization and match of hydraulic system delivers longer lasting performance
- ✔ Optimized electronic control system for better brake ability on a long downhill
- ✔ Improved steering mechanism reduces tire wear during turning
- ✔ Battery powered with zero emission and environmental-friendly

