



Hydraulic Motor Drive Scissor Lifts

PRODUCT SPECIFICATION

Model	CP1930	CP1932	CP2032	CP2632	CP2646	CP3246	CP3246	CP4046	CP4046	CP4550
Lift Capacity(Kg)	230	230	380	230	450	320	320	320	320	>10m 200 <10m 320
Lift Capacity Extension(Kg)	120	120	113	113	120	113	120	113	120	113
Max. Platform Occupants	2	2	2	2	2	2	2	2	2	2
Max. Working Height(A+2)(m)	7.8	7.8	7.9	10	10	12	12	14	14	15.8
Overall Length(B)(m)	1.83	1.83	2.4	2.4	2.49	2.47	2.49	2.47	2.49	2.79
Overall Width(C)(m)	0.76	0.81	0.83	0.83	1.18	1.18	1.18	1.18	1.18	1.27
Overall Height Rails Folded(m)	1.82	1.82	1.83	1.95	1.8	1.86	1.93	2.04	2.05	2.2
Overall Height Rails Unfolded(m)	2.12	2.12	2.19	2.32	2.38	2.43	2.5	2.62	2.65	2.72
Platform Extension Length(m)	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9	0.9
Driving Speed (stowed/raised)(km/h)	3.5/0.8	3.5/0.8	3.5/0.8	3.5/0.8	3/0.8	3.5/0.8	3/0.8	3.1/0.8	3/0.8	3.5/0.8
Up/Down Speed-GB(sec)	16/28	16/28	30/34	31/40	35/40	62/48	58/48	65/60	65/60	80/65
Up/Down Speed-CE(sec)	16/28	16/28	30/34	31/40	/	62/48	/	65/60	/	/
Gradeability(%)	25	25	25	25	25	25	25	25	25	25
Max. Slope(*)	1.5/3	1.5/3	1.5/3	1.5/3	1.5/3	2/3	1.5/3	1.5/3	1.5/3	1.5/3
Machine Weight(kg)	1,580	1,600	2,000	2,140	2350	2,610 3,000	2,855	3,380	2,990	3,535



- Most durable and reliable scissor stacks
- Reinforced working platform
- Advanced charger with voltage protection
- Higher driver comfort and security

