

ELEVATOR[®] 40 MOVE

Max. working height		4 m
Max capacity		200 kg
Number of people		1
Use		Internal
A	Closed machine height	1730 mm
B	Min. height from the ground*	290 mm
C	Maximum platform height	1950 mm
D	Base overall dimensions	1000 mm
E		715 mm
F	Cage dimensions	685 mm
G		580 mm
Machine weight		280 kg
Driving wheel size		Ø 186x60
Idle rear wheels size		Ø 150x40

PERFORMANCE

Power supply		24 V
Batteries		2 AGM 12V 45 Ah
Battery charger		115V–230V 50/60HZ
H1	Maximum climbing ability	15%
H2	Surmountable landing slope	15%
R1	Internal turning radius	900 mm
R2	External turning radius	1780 mm
Max. speed (rising)		0,15 m/s
Max. speed (descending)		0,15 m/s
Maximum shifting speed		5 km/h
I	Maximum pressure for wheel at full load **	1,6 kN

* There is an intermediate step.

** Maximum pressure whereas the weight of the platform plus the maximum load on the basket are completely distributed on one side of the platform (totally asymmetric load).



CE and TUV certified and approved for internal use in the absence of wind.
In assessing compliance, only those standards whose proposed measures have been implemented were considered and only if a corresponding risk does indeed exist.

