

KILMOON BUSINESS PARK, ASHBOURNE, CO. MEATH, A84 F776 TEL: 01 835 4788 sales@cherrypicker.ie

## Nifty 120T | 12.2m Trailer Mount

## KFY FFATURES

Working Height: 12.2m (40ft)

Working Outreach: 6.1m (20ft)

Telescopic Upper Boom

Greater accuracy when positioning platform

Bi-Energy Available

Optimising utilisation

**Hydraulic Outriggers** 

For quick & easy setup

Fully Proportional Hydraulic Controls

Simple, reliable & easy to maintain

Telescopic Axles

Access through double doorway openings#


**Traction Drive Option** 

Improved manoeuvrability on site.













The Nifty 120T trailer mount is specifically designed to give maximum reach performance from the most compact chassis possible.

By utilising its versatile telescopic upper boom, the Nifty 120T trailer mount delivers unrivalled working outreach, especially at lower levels where it's needed most.

Hydraulically operated outriggers make setting up the Nifty 120T trailer mount both quick and easy.

Telescopic axles coupled with a very compact base make the Nifty 120T trailer mount one of the most compact and manoeuvrable trailer mounts available.

The Nifty 120T trailer mount is also available with a traction drive option that offers a simple, cost effective and safe method for on-site positioning.



Working Height (A) 12.2m (40ft)




Traction Drive

Available



Platform Height (B) 10.2m (33ft 6in)





Outrigger Type Hydraulic



Machine Width (F) 1.5m (4ft 11in)



Retracted Width (E) 1.1m (3ft 7in)



Safe Working Load 200kg (440lbs)



Working Outreach (C) 6.1m (20ft)



Machine Height (D) 1.9m (6ft 3in)



Minimum Weight 1400kg (3100lbs)



Working Width (G) 3.55m (11ft 8in)




Cage Size

1.1m x 0.65m (3ft 7in x 2ft 2in)









Mains Only **Battery Only** Petrol or Diesel Only Bi-Energy (Engine & Battery)



